


480-500w

Quasar Module Series

N-BC HIGH EFFICIENCY 108-0BB-W-WG

Bloomberg NEW ENERGY FINANCE Tier 1 TOP PERFORMER 2026 kiwa PV MODULE RELIABILITY SCORECARD

Product Characteristics


- All back contact design enhances light absorption
- Aesthetic design in true black
- Optimized cell size brings higher power and lower transportation costs

Higher Quality Reliability

- Competitive high-temperature performance with ameliorated temperature coefficient
- Optimize power generation performance under partial shading conditions

Wider Application Conditions

- Universal solution for residential and C&I
- Easy for integration, designed for compatibility with existing mainstream inverters and diverse mounting systems



15-year Product Warranty

30-year Linear Performance Warranty

MANAGEMENT SYSTEM CERTIFICATES

IEC 61215, IEC 61730,

ISO 9001
2015 / Quality management system

ISO 14001
2015 / Standards for environmental management system

ISO 45001
2018 / International standards for occupational health & safety

GL-EN-VERSION 2026.06.16 © PHONO SOLAR CO., LTD. ALL RIGHTS RESERVED

www.phonosolar.com / info@phonosolar.com

Electrical Typical Values

Model	PS480L17GFH-18/VBH		PS485L17GFH-18/VBH		PS490L17GFH-18/VBH		PS495L17GFH-18/VBH		PS500L17GFH-18/VBH	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Rated Power (Pmpp)	480	365	485	369	490	373	495	377	500	387
Rated Current (Impp)	14.41	11.55	14.51	11.63	14.61	11.71	14.71	11.79	14.81	11.87
Rated Voltage (Vmpp)	33.32	31.60	33.43	31.52	33.54	31.85	33.66	31.98	33.77	32.10
Short Circuit Current (Isc)	15.11	12.14	15.21	12.22	15.31	12.30	15.41	12.38	15.51	12.46
Open Circuit Voltage (Voc)	40.27	38.10	40.42	38.27	40.56	38.34	40.72	38.60	40.86	38.75
Module Efficiency (%)	23.52		23.76		24.01		24.25		24.50	

STC (Standard Testing Conditions): Irradiance 1000W/m2 AM 1.5, Cell Temperature 25°c

NOCT (Nominal Operation Cell Temperature): Irradiance 800W/m2, Ambient Temperature 20°C , Spectra at AM1.5, Wind at 1m/s

Mechanical Characteristics

Cell Type	N Type BC
Dimension (L × W × H)	Length: 1800mm (70.87 inch) Width: 1134mm (44.65 inch) Height: 30mm (1.18 inch)
Weight	25kg (55.12 lbs)
Glass	2.0mm/2.0mm Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Cable (Including Connector)	4mm² (IEC), (+): 400mm,(-): 200mm or Customized Length
Junction Box	IP 68 Rated

Temperature Ratings

Voltage Temperature Coefficient	-0.20%/°C
Current Temperature Coefficient	+0.05%/°C
Power Temperature Coefficient	-0.26%/°C
Power Tolerance	0~+3%
NOCT	45±2°C
Bifaciality	70±5%


Absolute Maximum Rating


Operating Temperature	From -40 to + 85°C
Hail Diameter @ 80km/h	Up to 25mm
Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Maximum Series Fuse Rating	30A
PV Module Classification	II
Fire Rating (IEC61730)	C
Maximum System Voltage	DC 1500V


Packing Configuration

Container	40' HQ
Pcs/Container	864
Pcs/Pallet	36
Pallets/Container	24

Electrical Characteristics







PHONO

PHONO SOLAR TECHNOLOGY CO., LTD. reserves the right to make necessary adjustments to the information described herein at any time without further notice. The specifications and certificates contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Please be sure to use the most recent version of data.